



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012  
Date of issue: 01/29/2016 Revision date: 01/29/2016



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Low Alloy and Tool Steels  
Product code : AH0906K (US)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Ingots, Bar, Billet, Plate, Strip, Block, Electrode & Remelt Pig.

#### 1.3. Details of the supplier of the safety data sheet

Electralloy  
175 Main Street  
Oil City, PA 16301  
T 814-678-4100

#### 1.4. Emergency telephone number

Emergency number : 814-678-4200

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

This product, as sold, has little or no immediate health or fire hazards. Under OSHA 29 CFR 1910.1200 Hazardous Communication Standard, steel products are considered mixtures since in solution, the two or more substances do not react. If product is welded, burned, sawed, brazed, ground, etc. potentially hazardous airborne particulate matter and fumes may be generated. Such activities should be performed in well-ventilated areas with appropriate PPE, as per PPE assessments for tasks involved. The classification given below pertains to the product during processing:

#### GHS-US classification

Respiratory Sensitization 1  
Skin Sensitization 1  
Carcinogenicity 2  
Reproductive Toxicity 2  
Specific Target Organ Toxicity – Repeated Exposure 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Do not breathe dust/fume/gas/mist/vapors/spray. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace, but left there for cleaning. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available.

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable.



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable.

#### 3.2. Mixture

| Name                  | Product identifier             | %         | GHS-US classification   |
|-----------------------|--------------------------------|-----------|---|
| Iron (iron oxide)     | (CAS No) 7439-89-6 (1309-37-1) | 60 - 99.5 | Not classified.   |
| Tungsten              | (CAS No) 7440-33-7             | 0-21      | Flam. Sol. 1<br>Self-heat. 2  |
| Chromium <sup>1</sup> | (CAS No) 7440-47-3             | 0 - 20    | Not classified.   |
| Molybdenum            | (CAS No) 7439-98-7             | 0 - 15    | Combustible Dust  |
| Vanadium              | (CAS No) 7440-62-2             | 0 - 15    | Not classified.   |
| Cobalt                | (CAS No) 7440-48-4             | 0 - 13    | Resp. Sens. 1<br>Skin Sens. 1<br>Carc. 2<br>Repr. 2                                       |
| Nickel                | (CAS No) 7440-02-0             | 0 - 5     | Skin Sens. 1<br>Carc. 2<br>STOT RE 1  |
| Aluminum              | (CAS No) 7429-90-5             | 0 - 5     | Not classified.   |
| Manganese             | (CAS No) 7439-96-5             | 0 - 5     | STOT RE 2   |
| Silicon               | (CAS No) 7440-21-3             | 0 - 5     | Not classified.   |
| Carbon                | (CAS No) 7440-44-0             | 0 - 4     | Not classified.   |
| Copper                | (CAS No) 7440-50-8             | 0 - 1     | Not classified.   |
| Titanium              | (CAS No) 7440-32-6             | 0 - 1     | Not classified.   |
| Sulfur                | (CAS No) 7704-34-9             | 0-0.5     | Flam Sol 2  |
| Phosphorus            | (CAS No) 7723-14-0             | 0-0.5     | Pyr. Sol. 1<br>Acute Tox. 1 oral<br>Acute Tox. 4 inhalation<br>Skin Corr. 1A<br>STOT RE 1 |

The above listing is a summary of elements used in this product. Various grades will contain different combinations of these elements. Products of combustion may include, and are not limited to: oxides of various alloying elements and toxic metallic fumes.

The metal may contain small amounts of other elements in addition to those above. These elements, generally originate in small quantities in the raw material used. These elements may include, but are not limited to the following: Boron, Calcium, Tin and Zirconium.

<sup>1</sup> Welding, torch cutting, brazing, or grinding of chromium metal present in this product may generate airborne concentrations of hexavalent chromium.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                                       |   |
|---------------------------------------|---|
| First-aid measures after inhalation   | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.   |
| First-aid measures after skin contact | : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. Burns caused by molten material must be treated clinically. Do not use solvents or thinners. |
| First-aid measures after eye contact  | : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.   |
| First-aid measures after ingestion    | : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.  |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                                      |  |
|--------------------------------------|--|
| Symptoms/injuries after inhalation   | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. Dust and fumes may cause respiratory tract irritation. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath. Welding, torch cutting, brazing, or grinding of chromium metal present in this product may generate airborne concentrations of hexavalent chromium. |
| Symptoms/injuries after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skin contact. Risk of thermal burns on contact with molten product.  |
| Symptoms/injuries after eye contact  | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.  |
| Symptoms/injuries after ingestion    | : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.   |



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



Symptoms after chronic exposure : Excessive and repeated overexposure of nickel and chromium can cause various forms of dermatitis, inflammation and/or ulceration of upper respiratory tract. Both chromium and nickel have been associated with upper respiratory cancer. Excessive and repeated overexposure of iron fumes can cause siderosis. Excessive and prolonged inhalation of manganese fumes can cause bronchitis, pneumonitis, and lack of coordination.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.  
Unsuitable extinguishing media : Do not use water on molten metal as explosion hazard could result.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of various alloying elements and toxic metallic fumes.  
Explosion hazard : May be flammable and explosive when in dust cloud, depending on the concentration of the powder in a given area and the particle size of the powder.

### 5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### 6.2. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Do not use solvents or thinners.  
Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust, mist, gas, fume, vapors, spray. Do not swallow. Minimize generation of dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke. Use only in well-ventilated areas.  
Hygiene measures : Wash hands before eating, drinking, or smoking. Launder contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed, dry and in a well-ventilated place.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Iron (7439-89-6)       |                                     |   |
|------------------------|-------------------------------------|---|
| ACGIH                  | ACGIH TWA (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup>                       |
| OSHA                   | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup>                      |
| Iron Oxide (1309-37-1) |                                     |   |
| ACGIH                  | ACGIH TWA (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup> (respirable fraction) |



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



| <b>Iron Oxide (1309-37-1)</b> |   |   |
|-------------------------------|---|---|
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 10 mg/m <sup>3</sup> (fume);<br>15 mg/m <sup>3</sup> (total dust);<br>5 mg/m <sup>3</sup> (respirable fraction) |
| <b>Tungsten (7440-33-7)</b>   |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 5 mg/m <sup>3</sup>   |
| ACGIH                         | ACGIH STEL (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| OSHA                          | Not applicable                          |   |
| <b>Chromium (7440-47-3)</b>   |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 0.5 mg/m <sup>3</sup><br>0.5 mg/m <sup>3</sup> (as chromium III)  |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 1 mg/m <sup>3</sup><br>0.5 mg/m <sup>3</sup> (as chromium III)<br>5 µg/m <sup>3</sup> (as hexavalent chromium)  |
| <b>Molybdenum (7439-98-7)</b> |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup> (inhalable fraction)<br>3 mg/m <sup>3</sup> (respirable fraction)                          |
| OSHA                          | Not applicable                          |   |
| <b>Vanadium (7440-62-2)</b>   |   |   |
| ACGIH                         | Not applicable                          |   |
| OSHA                          | Not applicable                          |   |
| <b>Cobalt (7440-48-4)</b>     |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 0.02 mg/m <sup>3</sup>  |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 0.1 mg/m <sup>3</sup> (dust and fume)   |
| <b>Nickel (7440-02-0)</b>     |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 1.5 mg/m <sup>3</sup> (inhalable fraction)<br>0.2 mg/m <sup>3</sup> (as nickel oxide)                           |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 1 mg/m <sup>3</sup><br>1 mg/m <sup>3</sup> (as nickel oxide)  |
| <b>Aluminum (7429-90-5)</b>   |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 1 mg/m <sup>3</sup> (respirable fraction)   |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction)                                  |
| <b>Manganese (7439-96-5)</b>  |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 0.02 mg/m <sup>3</sup> (respirable fraction)<br>0.1 mg/m <sup>3</sup> (inhalable fraction)                      |
| OSHA                          | OSHA PEL (Ceiling) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> (fume)  |
| <b>Silicon (7440-21-3)</b>    |   |   |
| ACGIH                         | Not applicable                          |   |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction)                                  |
| <b>Carbon (7440-44-0)</b>     |   |   |
| ACGIH                         | Not applicable                          |   |
| OSHA                          | Not applicable                          |   |
| <b>Copper (7440-50-8)</b>     |   |   |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )          | 0.2 mg/m <sup>3</sup> (fume)  |



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



| Copper (7440-50-8)                  |                                     |  |
|-------------------------------------|-------------------------------------|--|
| OSHA                                | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 0.1 mg/m <sup>3</sup> (fume)<br>1 mg/m <sup>3</sup> (dust and mist)                    |
| Titanium (7440-32-6)                |                                     |  |
| ACGIH                               | Not applicable                      |  |
| OSHA                                | Not applicable                      |  |
| Sulfur (7704-34-9)                  |                                     |  |
| ACGIH                               | Not applicable                      |  |
| OSHA                                | Not applicable                      |  |
| Phosphorus (7723-14-0)              |                                     |  |
| ACGIH                               | Not applicable                      |  |
| OSHA                                | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 0.1 mg/m <sup>3</sup> (Phosphorus - yellow)  |
| Particulate not otherwise regulated |                                     |  |
| ACGIH                               | ACGIH TWA (mg/m <sup>3</sup> )      | 10 mg/m <sup>3</sup> (inhalable fraction)<br>3 mg/m <sup>3</sup> (respirable fraction) |
| OSHA                                | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction)         |

### 8.2. Exposure controls

|                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.  |
| Hand protection                  | : Wear chemically resistant protective gloves.  |
| Eye protection                   | : Safety glasses or goggles are recommended when using product.   |
| Skin and body protection         | : Wear suitable protective clothing.  |
| Respiratory protection           | : When dust and fumes are present from processing, a NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2). |
| Environmental exposure controls  | : Maintain levels below Community environmental protection thresholds.  |
| Other information                | : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.  |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |                               |
|--|-------------------------------|
| Physical state                             | : Solid                       |
| Appearance                                 | : No data available           |
| Colour                                     | : Metallic                    |
| Odour                                      | : Odorless                    |
| Odour threshold                            | : No data available           |
| pH   | : No data available           |
| Melting point                              | : 1427-1538 °C (2600-2800 °F) |
| Freezing point                             | : No data available           |
| Boiling point                              | : No data available           |
| Flash point                                | : No data available           |
| Relative evaporation rate (butylacetate=1) | : No data available           |
| Flammability (solid, gas)                  | : Not flammable               |
| Explosive limits                           | : No data available           |
| Explosive properties                       | : No data available           |
| Oxidising properties                       | : No data available           |
| Vapour pressure                            | : No data available           |



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



|  |                     |
|--|---------------------|
| Relative density                       | : 7.5-8.5           |
| Relative vapour density at 20 °C       | : No data available |
| Solubility                             | : Insoluble         |
| Partition coefficient: n-octanol/water | : No data available |
| Log Kow                                | : No data available |
| Auto-ignition temperature              | : No data available |
| Decomposition temperature              | : No data available |
| Viscosity                              | : No data available |
| Viscosity, kinematic                   | : No data available |
| Viscosity, dynamic                     | : No data available |

### 9.2. Other information

No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong acids. Oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of various alloying elements and toxic metallic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

| Low Alloy and Tool Steels |                |
|---------------------------|----------------|
| LD50 oral rat             | > 2000 mg/kg   |
| LD50 dermal rabbit        | > 2000 mg/kg   |
| LC50 inhalation rat       | > 5 mg/l/4h    |
| Iron (7439-89-6)          |                |
| LD50 oral rat             | > 5000 mg/kg   |
| Iron Oxide (1309-37-1)    |                |
| LD50 oral rat             | > 10000 mg/kg  |
| Chromium (7440-47-3)      |                |
| LD50 oral rat             | > 3400 mg/kg   |
| LC50 inhalation rat       | > 5.41 mg/l/4h |
| Molybdenum (7439-98-7)    |                |
| LD50 oral rat             | > 2000 mg/kg   |
| LD50 dermal rat           | > 2000 mg/kg   |
| LC50 inhalation rat       | > 5.0 mg/l/4h  |
| Cobalt (7440-48-4)        |                |
| LD50 oral rat             | 6170 mg/kg     |
| Nickel (7440-02-0)        |                |
| LD50 oral rat             | > 9000 mg/kg   |



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



| Aluminum (7429-90-5) |               |
|----------------------|---------------|
| LD50 oral rat        | > 10000 mg/kg |

| Manganese (7439-96-5) |                |
|-----------------------|----------------|
| LD50 oral rat         | >2000 mg/kg    |
| LC50 inhalation rat   | > 5.14 mg/l/4h |

| Silicon (7440-21-3) |              |
|---------------------|--------------|
| LD50 oral rat       | 3160 mg/kg   |
| LD50 dermal rabbit  | > 5000 mg/kg |

| Carbon (7440-44-0) |               |
|--------------------|---------------|
| LD50 oral rat      | > 10000 mg/kg |

| Copper (7440-50-8)  |                |
|---------------------|----------------|
| LD50 dermal rat     | > 2000 mg/kg   |
| LC50 inhalation rat | > 5.11 mg/l/4h |

| Sulfur (7704-34-9)  |               |
|---------------------|---------------|
| LD50 oral rat       | > 3000 mg/kg  |
| LD50 dermal rat     | > 2000 mg/kg  |
| LC50 inhalation rat | >9.23 mg/l/4h |

| Phosphorus (7723-14-0) |             |
|------------------------|-------------|
| LD50 oral rat          | 3.03 mg/kg  |
| LD50 dermal rat        | 100 mg/kg   |
| LC50 inhalation rat    | 4.3 mg/l/1h |

- Skin corrosion/irritation : Based on available data, the classification criteria are not met.
- Serious eye damage/irritation : Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- Germ cell mutagenicity : Based on available data, the classification criteria are not met.
- Carcinogenicity : Suspected of causing cancer.

| Chromium (7440-47-3) |                      |
|----------------------|----------------------|
| IARC group           | 3 - Not classifiable |

| Cobalt (7440-48-4)                       |                                      |
|--|--------------------------------------|
| IARC group                               | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity      |

| Nickel (7440-02-0)                       |   |
|--|---|
| IARC group                               | 2B - Possibly carcinogenic to humans              |
| National Toxicology Program (NTP) Status | 3 - Reasonably anticipated to be Human Carcinogen |

- Reproductive toxicity : Suspected of damaging fertility or the unborn child.
- Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.
- Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.
- Aspiration hazard : Based on available data, the classification criteria are not met.
- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. Dust and fumes may cause respiratory tract irritation. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath. Welding, torch cutting, brazing, or grinding of chromium metal present in this product may generate airborne concentrations of hexavalent chromium.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skin contact. Risk of thermal burns on contact with molten product.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.



# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



Symptoms after chronic exposure : Excessive and repeated overexposure of nickel and chromium can cause various forms of dermatitis, inflammation and/or ulceration of upper respiratory tract. Both chromium and nickel have been associated with upper respiratory cancer. Excessive and repeated overexposure of iron fumes can cause siderosis. Excessive and prolonged inhalation of manganese fumes can cause bronchitis, pneumonitis, and lack of coordination.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 12.2. Persistence and degradability

| Low Alloy and Tool Steels     |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

#### 12.3. Bioaccumulative potential

| Low Alloy and Tool Steels |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

#### 12.4. Mobility in soil

No additional information available.

#### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT.

As shipped, not regulated for transport.

#### Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

| Chromium (7440-47-3)  |  |
|-----------------------|--|
| Regulations           | CAA, CWA, SARA 313, SDWA, CERCLA, RCRA |
| Cobalt (7440-48-4)    |  |
| Regulations           | SARA 313                               |
| Nickel (7440-02-0)    |  |
| Regulations           | CAA, CWA, SARA 313, CERCLA, SDWA, RCRA |
| Aluminum (7429-90-5)  |  |
| Regulations           | SWDA, SARA 313                         |
| Manganese (7439-96-5) |  |
| Regulations           | SARA 313, CAA, CERCLA, SDWA            |
| Vanadium (7440-62-2)  |  |
| Regulations           | SARA 313, CERCLA, SDWA, RCRA           |
| Copper (7440-50-8)    |  |
| Regulations           | CWA, CERCLA, SDWA, SARA 313            |





# Low Alloy and Tool Steels

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



### Phosphorus (7723-14-0)

|             |                                  |
|-------------|----------------------------------|
| Regulations | CAA, CWA, SARA 313, CERCLA, SDWA |
|-------------|----------------------------------|

### 15.2. US State regulations

#### Low Alloy and Tool Steels

|                            |   |
|----------------------------|---|
| State or local regulations | This product contains chemicals known to the State of California to cause cancer. |
|----------------------------|---|

### SECTION 16: Other information

|                   |              |
|-------------------|--------------|
| Date of issue     | : 01/29/2016 |
| Revision date     | : 01/29/2016 |
| Version           | : K          |
| Other information | : None       |

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy one-self as to the suitability and completeness of this information for the user's own particular use.*